

# COMPAC

HOME PRODUCTS SALES SERVICE ABOUT US CONTACT



[CLICK HERE to go back to Products page](#)

[DOWNLOAD PARTS AND SERVICE MANUAL](#)

## T175 Static Roller Two Ton 18 H.P Static Roller

- 2700 lbs of applied force rear roll
- 25" diameter, 38" wide rear roll
- 42" Wide x 84" Long x 59" High

## T175 Vibratory Compactor Two Ton 18 H.P Asphalt and Aggregate Vibratory Compactor

- 6340 lbs of applied force rear roll
- 25" diameter, 38" wide rear roll
- 42" Wide x 81" Long x 59" High
- Direct drive vibration eliminates V-belt
- Oil bath vibratory bearings

## T175S/T175V Features

- Big 18 H.P twin cylinder engine with oil pump pressure lubrication and spin-on filter
- Transmission by-pass: Simple operation
- Traction & gradeability are the best in their class because over 75% of machine weight is on the rear roll
- Tightest turning radius - 20in inside
- Ergonomically designed for operator ease and comfort
- Compact size - 16in shorter than other popular roller
- Huge polyethylene black water tank - rust and algae free
- All-weather marine ignition switch
- Low, easy maintenance - only two grease fitting
- Vandal protected - lockable engine cover
- 24 month warranty



## Options

Pressure Spray System, ROPS, Backup Alarm, Increased Working Weight, Hour Meter, Gauges, Sound Attenuation

<b>DIMENSIONS</b>	<b>COMPAC T175S</b>	<b>COMPAC T175V</b>
Overall Length	84 in	81 in
Overall Width	42 in	42 in
Overall Height	59 in	59 in
Curb Clearance	15.5 in	13.5 in
Wall Clearance	5/8 in	5/8 in

<b>PERFORMANCE &amp; SPECIFICATIONS</b>	<b>COMPAC T175S</b>	<b>COMPAC T175V</b>
Shipping Weight	2,100 lbs	2,640 lbs
Operating Weight	2,600 lbs	3,140 lbs
Vibration Frequency	N/A	3,400 vpm
Compaction Roll	1800 lbs	2340 lbs
Applied Force	1800 lbs	6344 lbs
Centrifugal Force	N/A	4,000 lbs
Amplitude	N/A	.020 in
Water Tank Capacity	45 gal	45 gal
Hydraulic Tank Capacity	7 gal	7 gal
Engine	20 HP	
Speed	6 mph	6 mph
Gradeability*	73 %	61 %
Inside Turning Radius	20 in	20 in

\*Gradeability is determined by traction and the rolling resistance of the material.